



## QUALITIUM GEAR CVT

*Technologically advanced, fully synthetic oil for automatic gear boxes type CVT (Continuously Variable Transmission)*

### APPLICATION

- high-quality synthetic gear oil designed for the latest generation of automatic continuously variable gear boxes type CVT
- meets requirement many specification OEM's
- do not mix with other ATF type oils.
- CVT oils should not be used in DCT type automatic transmissions

### ADVANTAGES

*Qualitium Gear CVT provides consistent all-weather smooth shifting and lubrication protection of the transmission components to help extend transmission service life and provide a comfortable driving experience*

- stable, optimised friction characteristics and outstanding torque capacity retention provide smooth shift feel without noise and vibration concerns
- extends life time duration due to high shear stability at hot temperature and high oxidation resistance
- increases wear protection of belt, chain and pulleys
- excellent flow properties provide immediate lubrication and protection at cold start-up

### SPECIFICATIONS

Page 2

### REPLACEMENT OILS

Mobil	Fuchs	Castrol
CVTF Multi-vehicle	Titan CVTF Flex	Transmax CVT
TotalEnergies	Orlen Oil	Shell
Fluidmatic CVT MV	Gear CVT Gear CVT Hybrid	Spirax S5 CVT X

### AVAILABLE OIL VOLUMES

1L, 4L, 20L, 205L, 1000L

Parameters	Value
Kinematic viscosity at 100°C (mm <sup>2</sup> /s)	<b>7.3</b>
Viscosity index	<b>180</b>
Flash point (COC, °C)	<b>206</b>
Pour point (°C)	<b>-51</b>

\* The above are typical physicochemical values. The actual physicochemical values are to be found in the laboratory report attached to each batch of the product.

### DETAILS OF THE COMPANY/TECHNICAL DEPARTMENT

Qualitium Sp. z o.o.  
Brzeście Nowe 11B/2, 09-130 Baboszewo

Guaranteed storage period 3 years from production date. Production date and batch number are on the packaging.

<b>OEM</b>	<b>Specification</b>
Daihatsu	Ammix CVTF DFE
Daihatsu	Ammix CVTF DTC
Dodge/Chrysler/Jeep	CVTF+4, P/N 05191184AA
Dodge/Jeep/Chrysler	NS-2
Ford	Merc C, P/N XT-7-QCFT, Spec. WSS-M2C933-A, CFT30
Ford	Spec. WSS-M2C928-A, CFT23
GM	Dex-CVT Fluid, Saturn P/N 22688912
GM	GM CVTF I-Green2
GM	AC Delco CVT Fluid P/N 19260800
Honda/Acura	HCF-2 P/N 08200-HCF2
Honda/Acura	CVT-1 P/N 08200-9006
Honda/Acura	CVT Fluid
Hyundai/Kia	CVTF-J1
Mazda	CVTF 3320
Mercedes	MB 236.20 CVT
Mini	CVT EZL 799A Fluid, P/N, 83 22 0 136 376, 83 22 2 344 207, 83 22 0 429 154
Mitsubishi	Dia Queen CVTF-J1
Mitsubishi	Dia Queen CVTF-J4, P/N MZ320185
Mitsubishi	Dia Queen CVTF-J4+, P/N MZ102652
Mitsubishi	CVTF-ECO J4, P/N MZ320262
Nissan	CVT fluid NS-1
Nissan	CVT fluid NS-2
Nissan	CVT fluid NS-2V
Nissan	CVT fluid NS-3
PUNCH	CVTF EZL 799A
PUNCH	CVT-PPT
Renault	Matic CVT FK/CK/DK, ELFMATIC CVT
Subaru	High Torque CVT P/N K0421Y0700
Subaru	CVTF-II for Lineartronic II, P/N K0425Y0711
Subaru	CVTF for Lineartronic, P/N K0425Y0710
Subaru	i-CVTF, P/N K0415YA090
Subaru	i-CVTF FG, P/N K0414Y0710
Subaru	e-CVTF
Suzuki	CVT Fluid Green 1, Shell Green 1V
Suzuki	CVT Fluid Green 2
Suzuki	Su-CVT fluid
Suzuki	VTF 3320, TC
Toyota	CVT Fluid type FE
Toyota	CVT Fluid TC
VW/Audi	G 052 180 (-A2)
VW/Audi	G 052 516 (-A2)