

# QUALITIUM POWER LV 0W/20



**Technologically advanced, fully synthetic motor oil for passenger cars and light commercial vehicles with VW 508.00/509.00 specification**



## **SPECIFICATIONS**

SAE: 0W/20

ACEA: C5

API: SP/SN-Plus

ILSAC: GF-6A

## **MEETS REQUIREMENTS**

Volkswagen VW 508.00/509.00

Ford WSS -M2C956-A1

Porsche C20

May be used in the following vehicles: **AUDI, BMW, CHEVROLET, CHRYSLER, CITROEN, DACIA, DAEWOO, FIAT, FORD, HONDA, HYUNDAI, KIA, MERCEDES, MITSUBISHI, OPEL, PEUGEOT, RENAULT, ROVER, SAAB, SEAT, SKODA, SUBARU, TOYOTA, VOLKSWAGEN, VOLVO** and others when oil of this grade is recommended.

## **REPLACEMENT OILS**

Mobil	Shell	Castrol
Mobil 1 ESP X2 0W/20 Super 3000 Formula V 0W/20	Helix Ultra Professional AV-L 0W/20	Edge 0W/20 LL IV
Elf/TotalEnergies	Orlen Oil	Texaco
Evolution Full-Tech VSX 0W/20 Quartz Ineo Xtra Longlife 0W/20	Max Expert LL 0W/20 Quazar Dynamic 508/509 0W/20	Havoline ProDS VB 0W/20

## **AVAILABLE OIL VOLUMES**

1L, 4L, 20L, 60L, 205L, 1000L

## **APPLICATION**

- Volkswagen passenger cars and light commercial vehicles or vans requiring VW 508.00/509.00
- Passenger cars and light commercial vehicles or vans requiring ACEA C5 for compatibility with GPF or DPF
- is recommended for the new high-performance gasoline, diesel and hybrid engines found in emerging European vehicles that require SAE 0W-20
- for engines satisfying Euro 6 emission standards

## **ADVANTAGES**

**Qualitium Power LV 0W/20 new generation, technologically advanced oil with standards ACEA C5 and VW 508.00/509.00 for most modern vehicles requiring low viscosity oil**

- perfectly removes solid impurities and reduces the formation of deposits on the pistons and the turbocharger.
- Provides up to 4% fuel economy improvement when changing from a higher viscosity 5W-30 engine oil
- Quick cold weather performance to help provide fast protection at start-up
- improved properties in terms of oil flow and "adhesion" to lubricated elements are ideal for vehicles with start-stop systems

Parameters	Value
Kinematic viscosity at 100°C (mm <sup>2</sup> /s)	<b>8.7</b>
Viscosity index	<b>172</b>
Flash point (COC, °C)	<b>218</b>
Pour point (°C)	<b>-50</b>
Total Basic Number (TBN, mg KOH/g)	<b>7.5</b>

\* The above are typical physicochemical values. The actual physicochemical values are to be found in the laboratory report attached to each batch of the product.

## **DETAILS OF THE COMPANY/TECHNICAL DEPARTMENT**

Qualitium Sp. z o.o.

Brzeście Nowe 11B/2, 09-130 Baboszewo

Guaranteed storage period 3 years from production date. Production date and batch number are on the packaging.