

QUALITIUM POWER R 5W/30

Premium quality, synthetic motor oil for passenger cars and light commercial vehicles.



SPECIFICATIONS

SAE: 5W/30

API: SN/SN+

ACEA: C3

MEETS REQUIREMENTS

RN 17

MB 229.31

MB 229.51

MB 229.52

BMW Longlife-04

May be used in the following vehicles: **AUDI, BMW, CHEVROLET, CHRYSLER, CITROEN, DACIA, DAEWOO, FIAT, FORD, HONDA, HYUNDAI, KIA, ŁADA, MERCEDES, MITSUBISHI, OPEL, PEUGEOT, RENAULT, ROVER, SAAB, SEAT, SKODA, SUBARU, TOYOTA, VOLKSWAGEN, VOLVO** and others when oil of this grade is recommended.

REPLACEMENT OILS

Mobil	Shell	Castrol
Super 3000 Formula RN 5W/30	Helix Ultra Professional AR-L RN17 5W/30	GTX 5W/30 RN 17
Elf/TotalEnergies	Orlen Oil	Texaco
Evolution Full-Tech R 5W/30 Quartz Ineo R-Plus 5W/30	-	Havoline Energy EF 5W/30

AVAILABLE OIL VOLUMES

1L, 5L, 20L, 60L, 205L, 1000L

APPLICATION

- Renault passenger cars and light commercial vehicles or vans requiring RN17
- passenger cars and light commercial vehicles or vans with exhaust reduction systems such as DPF or TWC
- for diesels and petrol engines
- for engines satisfying Euro 6 emission standards

ADVANTAGES

Qualitium Power R 5W/30 new generation oil with standards ACEA C3 and Renault RN17 for most modern vehicles with exhaust reduction systems such as DPF or TWC

- perfectly removes solid impurities and reduces the formation of deposits on the pistons and the turbocharger.
- delivers unsurpassed levels of protection across a variety of driving conditions and temperatures
- improved properties in terms of oil flow and "adhesion" to lubricated elements are ideal for vehicles with start-stop systems

Parameters	Value
Kinematic viscosity at 100°C (mm ² /s)	11.1
Viscosity index	165
Flash point (COC, °C)	220
Pour point (°C)	-39
Total Basic Number (TBN, mg KOH/g)	7.8

* The above are typical physicochemical values. The actual physicochemical values are to be found in the laboratory report attached to each batch of the product.

DETAILS OF THE COMPANY/TECHNICAL DEPARTMENT

Qualitium Sp. z o.o.

Brzeście Nowe 11B/2, 09-130 Baboszewo

Guaranteed storage period 3 years from production date. Production date and batch number are on the packaging.