

PILAK PLUS

VG: 68, 80, 100, 150

APPLICATION

PILAK PLUS VG: 68, PILAK PLUS VG: 80, PILAK PLUS VG: 100, PILAK PLUS VG: 150 are a special, multi-grade oils used for the lubrication cutting systems (chain) and mechanical saw guides used in forestry, horticulture and households. It is also intended for lubrication in other cutting devices, in machines used in felling trees, as well as for transport chains and machine components.

ADVANTAGES

- Excellent lubricating properties - prevents jamming or breaking the chain
- Protects against corrosion and abrasive wear
- Stability of parameters both at low and high operating temperatures



STANDARDS, SPECIFICATIONS

ISO VG 68, 80, 100, 150

* **The colour of PILAK PLUS oil can be modified to the individual customer's order.**

PARAMETRY	PILAK PLUS			
	VG: 68	VG: 80	VG: 100	VG: 150
Kinematic viscosity at 40°C, [mm ² /s]	65,0	80,1	104,7	150,5
Viscosity index	130	148	156	120
Flash point, [°C]	220	220	224	236
Pour point, [°C]	-27	-21	-18	-15
Colour*	yellow, green, dark green			
Notice: The above parameter values are typical. The actual values are to be found in the laboratory report attached to each batch of the product.				

Guaranteed storage period 3 years from production date. Production date and batch number are on the packaging.