

# QUALITIUM AGRI STOU PLUS 10W/40



**New generation, multifunctional STOU oil based on advanced technology containing synthetic oils and selected additives.**

## **SPECIFICATIONS**

API: CG-4/CF-4/CF/SF

API: GL-4

ACEA: E3/E5

SAE: 10W/40

ISO HV

## **MEETS REQUIREMENTS**

Allison C-4

Caterpillar TO-2

Case New Holland (CNH) MAT 3525/3526

Ford M2C159-C, M2C134-D, M2C48-C3

J.I Case MS-1204/6/7/9

John Deere J27/J20D/J20C

Massey Ferguson M1135/M1139/M1143/  
M1144/M1145

MB 227.1/228.1/228.3

MAN 271

New Holland 82009201/2/3, 410C, 330H

ZF-TE ML 06A/06B/06C/06D/07B

MIL-L-2104D

May be used in the following vehicles:

**AGCO, BELARUS, CASE, CLASS, DEUTZ-FAHR, DRESSER, FENDT, FIAT, HOLDER, HARVESTER, HYUNDAI, JCB, JOHN-DEERE, KUHN, KUBOTA, LAMBORGHINI, LANDINI, MARSHALL, MASSEY-FERGUSON, MITSUBISHI, NEW HOLLAND, PRONAR, RENAULT, STEYER, URSUS, VERMEER, ZETOR** and others when oil of this grade is recommended.

## **APPLICATION**

- new generation of engine, transmission, and hydraulic oil for agricultural and construction machinery that meets the standards of many equipment manufacturers
- for modern engines in agricultural and construction machinery operating in difficult and extremely difficult conditions
- for manual transmissions operating in very difficult operating conditions
- hydrokinetic transmissions
- hydraulic systems
- wet clutches and brakes

## **ADVANTAGES**

- addition of synthetic bases and new-generation additives ensures excellent engine cleanliness even under extremely difficult operating conditions
- high viscosity index indicates that the oil can be used across a wide temperature range
- ensures precise lubrication between interacting components
- one oil for all lubrication systems in modern tractors, reducing the possibility of errors
- optimal operation of transmissions, clutches, and wet brakes
- contains an appropriate additive package and can be used in systems with "Limited Slip" requirements
- minimal oil loss, resulting in smaller refills and savings

Parameters	Value
Kinematic viscosity at 100°C (mm <sup>2</sup> /s)	14.5
Viscosity index	160
Flash point (COC, °C)	228
Pour point (°C)	-45
Total Basic Number (TBN, mg KOH/g)	11.7

\* The above are typical physicochemical values. The actual physicochemical values are to be found in the laboratory report attached to each batch of the product.

## **AVAILABLE OIL VOLUMES**

20L, 205L, 1000L

## **DETAILS OF THE COMPANY/TECHNICAL DEPARTMENT**

Qualitium Sp. z o.o.

Brzeście Nowe 11B/2, 09-130 Baboszewo

Guaranteed storage period 3 years from production date.  
Production date and batch number are on the packaging.