

QUALITIUM MOTO 4T 20W/50

Engine oil for motorcycles.



STANDARDS/SPECIFICATIONS

SAE: 20W/50

API: SL/SJ

JASO MA2

JASO T903

May be used in motorcycles:

BMW, DUCATI, HONDA, KAWASAKI, SUZUKI, YAMAHA and others when oil of this grade is recommended.

AVAILABLE OIL VOLUMES

1L, 5L, 20L, 60L, 205L

APPLICATION

- four-stroke engines of sport, cruiser and touring motorcycles, as well as quads
- performs brilliantly in motorcycle transmissions and wet clutch transmissions

ADVANTAGES

Qualitium Moto 4T 20W/50 ensures ideal anti-wear protection, reduces wear of engine elements by at least 20% in comparison to corresponding oils.

- ensures excellent engine protection – extending its life to a maximum
- very good anti-wear properties
- allows to reach the maximum engine power at high temperatures
- excellent lubrication of engine even in extreme operating conditions

Parameters	Value
Kinematic viscosity at 100°C (mm ² /s)	18.3
Viscosity index	144
Flash point (COC, °C)	230
Pour point (°C)	-30

* The above are typical physicochemical values. The actual physicochemical values are to be found in the laboratory report attached to each batch of the product.

DETAILS OF THE COMPANY/TECHNICAL DEPARTMENT

Qualitium Sp. z o.o.

Brzeście Nowe 11B/2, 09-130 Baboszewo

Guaranteed storage period 3 years from production date. Production date and batch number are on the packaging.