



QUALITIUM SYNTHETIC A5/B5 0W/30

Synthetic motor oil for passenger cars and light commercial vehicles.

APPLICATION

- meets requirements VOLVO VCC 95200377
- passenger cars and light commercial vehicles
- for diesels and petrol engines
- turbocharged engines and direct injection engines
- severe operating conditions – frequent rides on highways and in city traffic

SPECIFICATIONS

SAE: 0W/30

API: SL/CF

ACEA: A5/B5

MEETS REQUIREMENTS

VOLVO VCC 95200377

MB 229.6

Ford WSS- M2C913-D

STJLR 03.5003

May be used in the following vehicles:

AUDI, BMW, CHEVROLET, CHRYSLER, CITROEN, DACIA, DAEWOO, FIAT, FORD, HONDA, HYUNDAI, KIA, ŁADA, MAZDA, MERCEDES, MITSUBISHI, NISSAN, OPEL, PEUGEOT, RENAULT, ROVER, SAAB, SEAT, SKODA, SUBARU, SUZUKI, TOYOTA, VOLKSWAGEN, VOLVO and others when oil of this grade is recommended.

REPLACEMENT OILS

Castrol Edge 0W/30 A5/B5

Mobil 1 ESP LV 0W/30

Motul 8100 Eco-Nergy 0W/30

Total Quartz 9000 0W/30

Orlen Oil Max Expert A5/B5 0W/30

Texaco Havoline Energy 0W/30

Fuchs Titan Supersyn FE 0W/30

AVAILABLE OIL VOLUMES

1L, 5L, 60L, 205L, 1000L

ADVANTAGES

Qualitium Synthetic A5/B5 0W/30 - excellent overall lubrication and wear protection and fuel economy min. 2,5%.

- advanced full synthetic formulation
- maximum extension of engine life
- fast flow to lubrication pairs at very low ambient temperatures – in severe winter conditions
- contributes to fuel economy by reducing friction
- allows developing maximum power of the engine
- prevents deposition of contaminants in the engine

Parameters	Value
Kinematic viscosity at 100°C (mm ² /s)	11,0
Viscosity index	180
Flash point (COC, °C)	226
Pour point (°C)	-42
Viscosity CCS at -35 °C (mPas)	5950

* The above are typical physicochemical values. The actual physicochemical values are to be found in the laboratory report attached to each batch of the product.

DETAILS OF THE COMPANY/TECHNICAL DEPARTMENT

Qualitium Sp. z o.o.

Brzeście Nowe 11B/2, 09-130 Baboszewo

Guaranteed storage period 3 years from production date. Production date and batch number are on the packaging.